

Name of work:- **P & F interlocking Pathway and M.S. main Gate in Chemical Engineering Department (Eastern Wing) at MNIT Campus Jaipur.**

G-Schedule

S.No	Qty	Items	Unit	Rate	Amount
1	24.42	Earth work in surface excavation not exceeding 30cm. in depth but exceeding 1.5 meter in width as well as 10 Sqm on plan including disposal of excavated earth up to 50 Mtr. and lift up to 1.5 Mtr. disposed soil to be levelled and neatly dressed: All kinds of soil	Sqm	31.00	757.02
2	2.44	Filling available excavated earth (excluding rock) in trenches, plinth side of foundation etc. in layers not exceeding 20 cm. in depth, consolidating each deposited layer by ramming and watering including lead up to 50 meter and with all lift.	Cum	56.00	136.64
3		Providing and laying in position cement concrete including curing, compaction etc. complete in specified grade excluding the cost of centering and shuttering - All work up to plinth level.			
A	1.65	M10 grade Nominal Mix	Cum	3331.00	5496.15
B	2.44	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size).	Cum	2859.00	6975.96
4	243.2	Providing and fixing steel gate, grating, and grills made of angles, tees, square bars, flats, or black pipe with holdfast and fittings complete as per design and drawing including cutting welding and fabrication with priming coat of red oxide	Kg.	83.00	20185.60
5	243.2	Extra if square, rectangular hollow tubular sections are used or grill made by flats only	Kg.	8.3	2018.56
6		Providing and laying of paver block as per IS 15658 : 2006 (Indian standard for precast concrete block for paving-specification) and IRC : SP:63-2004 (guidelines for the use of interlocking concrete block pavement)			
A	284.9	M-30, 60 mm thick to be used in non traffic areas like building Category 'B' Denoted only two side like I,Z,T shape etc. as per IRC SP 63:2004	Sqm	716.00	203988.40

7	6.18	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement in position to the required line, level and curvature jointed with cement mortar 1:3 (1 cement : 3 coarse sand) including making joints with without grooves (thickness of joints except at sharp curve shall not to more than 5mm) including making drainage opening wherever required complete including painting etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast C.C. kerb stone shall be approved by Engineer-in-charge).	Cum	5416.00	33470.88
8		Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :			
A	78.76	Two or more coats on new work	Sqm	60.00	4725.60
		TOTAL			277754.81
		SAY			277755.00
					RS

**EXECUTIVE ENGINEER
ESTATE SECTION MNIT
JAIPUR**

I/We hereby agree to execute the work @.....%Above/Below of Schedule 'G'

SIGNATURE OF THE CONTRACTOR WITH FULL POSTAL ADDRESS